GLOBE CONE FLOOR



In our perpetual quest for the purest forms, Globe stands out as the most minimal of the lot. A spherical orb, highly mirrored and perfectly reflective during the day, when switched on reveals a multiplicity of internal reflections from the integral LED. Globe is available in copper and chrome finishes in pendant form and a floor light.

 Year of Design
 2019

 Material
 Polycarbonate, steel and carbon fibre

 LED Spec
 Integrated, serviceable LED. 800 lumens. 3000K. CRI ≥

 Cable Spec
 80. 250cm/98.4in black fabric cable with foot switch

 Dimmability
 Mains dimmable.

 Rating/Location
 Dry

50/19.7"

22/8.7"

180/70.9″

GLOBE CONE FLOOR CHROME BLACK UL

Code GLS02CH-PUSM1 Components GLS02CH CONF01BKUL

GLOBE CONE FLOOR COPPER BLACK UL

Code GLS02CO-PUSM1 Components GLS02CO CONF01BKUL

GLOBE CONE FLOOR

Process		
Blow moulded polycarbonate with a semi	Packaging GLS02CH	
metallised interior and injection moulded		23"
polycarbonate diffuser.	Height Width	25"
		21.5
Cleaning Instructions	Length Weight	21.5 8lb
Clean with a soft dry cloth only. Do not use	5	OID
polishing agents, water or abrasive materials	GLS02CO	
	Height	23"
when cleaning. Always switch off the electricity	Width	21.5'"
supply before cleaning.	Length	21.5"
	Weight	8lb
Country of origin	CONF01BKUL	
Germany	Height	55"
	Width	10"
	Length	10"
	Weight	14lb
	Product weight 15.51b Requires assembly	
	Yes	,
	Light Source Included	
	6W Tom Dixon LED Ring	

Voltage 220-240V



tomdixon.net

2

GLOBE PENDANT 50CM



In our perpetual quest for the purest forms, Globe stands out as the most minimal of the lot. A spherical orb, highly mirrored and perfectly reflective during the day, when switched on reveals a multiplicity of internal reflections from the integral LED. Globe is available in copper and chrome finishes in pendant form and a floor light.

> Polycarbonate, steel and carbon fibre Integrated, serviceable LED, 800 lumens, 3000K,

CRI ≥ 80. 250cm / 98.4in clear cable.

Year of Design	2019
Material	Polyc
LED Spec	Integ
Cable Spec	CRI ≥
Dimmability	Main
Rating/Location	IP20

·@.

2019

Mains dimmable.

GLOBE PENDANT CHROME 50CM UL Code

GLS02CH-PUSM1 Components GLS02CH LEDP04BKUL

GLOBE PENDANT COPPER 50CM UL

Code GLS02CO-PUSM1 Components GLS02CO LEDP04BKUL

Process

Blow moulded polycarbonate with a semi metallised interior and injection moulded polycarbonate diffuser.

GLOBE PENDANT 50CM

Cleaning Instructions

Clean with a soft dry cloth only.Do not use polishing agents, water or abrasive materials when cleaning. Always switch off the electricity supply before cleaning.

Country of origin Germany

Packaging

GLS02CO	
Height	22"
Width	21"
Length	21"
Weight	8.2 lb

LEDP04BKUL

Height	5"
Width	8"
Length	12.5"
Weight	2.9lb

Product weight 5.7lb

Ceiling rose Polished Chrome Steel Dome 12.5cm/4.9in Ø Polished Copper Steel Dome 12.5cm/4.9in Ø

Requires assembly


Yes

Light Source Included

6W Tom Dixon LED Ring

Voltage

220-240V





tomdixon.net

1